

ARMSTRONG'S SEMI-SOLID WOOD STAIN

OXFORD BROWN – MOUNTAIN CEDAR – SEQUOIA – WOODLAND BROWN

PRODUCT DATA SHEET

DESCRIPTION: A one coat, high solids pigmented finish made from heavy and light bodied oils with four times the pigments of our semi-transparent stains designed for application on unpainted wood. Heavy bodied oils provide water repellency. Extra pigments provide longer lasting sun protection. Light bodied oils combined with solvent penetrate deep into the wood. Armstrong's Semi-Transparent Wood Stains repel water, add flexibility to the wood and reflect a greater degree of the sun's UV rays.

UNIQUE QUALITIES: Armstrong's formula is a combination of drying and non-drying oils that gives the user two layers of protection with one brush stroke. Armstrong's Wood Stains have non-drying conditioning oils that separate from the drying side of the formula. These oils penetrate deep into the wood fiber where the wood's natural oils used to be. This process rejuvenates the wood. The drying oils stay at the surface, lock in the conditioning oils and create a barrier that is dry to the touch. Armstrong's Wood Stains have only a mild boiled linseed oil aroma and can be applied in the direct sunlight/heat of the day.

USE: For all new, old and pressure treated unpainted wood surfaces such as: decks, siding, shakes and shingles, fences and log homes where color retention, water repellency and wood conditioning is the desired goal.

SURFACE PREPARATION: Surface must be clean, dry and free of dust and dirt. Wash surface with Armstrong's Concentrated Wood Cleaner or pressure wash. Previously stained surfaces should be tested with Armstrong's Wood Stain prior to an entire application to assure penetration and finish appearance.

APPLICATION: Easy application by brush, roller or airless spray equipment. Back brushing or back rolling recommended with spray applications. After 24 hours, remove any wet spots with a dry towel. See rag disposal cautions on the can label. Reapply at 5 to 6 year intervals for vertical surfaces and 2 to 4 year intervals for horizontal surfaces, depending upon weather exposure.

CLEAN UP: Clean all equipment with paint thinner. All empty cans must be air dried. Dispose according to state and local regulations.

ARMSTRONG'S SEMI-SOLID WOOD STAIN

OXFORD BROWN – MOUNTAIN CEDAR – SEQUOIA – WOODLAND BROWN

GENERAL PROPERTIES

VOC:	Does not exceed 250 grams per liter
TYPE:	Linseed oil based
DRY TIME:	Allow 36 to 48 hours dry time before heavy use
COVERAGE:	Approximately 200 square feet per gallon horizontal and approximately 400 square feet per gallon vertical, depending on age and porosity of wood
THINNER:	DO NOT THIN
FLASH POINT RANGE:	165° F to 172° F closed cup
SOLIDS:	75% active ingredients
CUSTOM COLORS:	Armstrong's Wood Stains are <u>NOT TINTABLE</u> however, Armstrong's Transparent and Semi-Transparent and Semi-Solid Wood Stains can be intermixed to create custom colors.
APPLICATION TEMPERATURE RANGE:	50° F to 120° F