

ARMSTRONG'S WOOD STAINS

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations
Revision Date: 02/23/2018 Date of issue: 08/18/2015

Version: 1.0

SECTION 1: IDENTIFICATION

1.1. Product Identifier

Product Form: Mixture

Product Name: ARMSTRONG-CLARK WOOD STAINS

1.2. Intended Use of the Product

Use of the substance/mixture: WOOD STAIN

1.3. Name, Address, and Telephone of the Responsible Party

Company

Armstrong Clark Company

14949 Camage Ave.

Sonora, CA 95370

1.4. Emergency Telephone Number: CHEMTREC 1-800-424-9300

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the Substance or Mixture

Classification (GHS-US)

Eye Irrit. 2A H319

Skin Sens. 1 H317

Carc. 1B H350

STOT RE 2 H373

Asp. Tox. 1 H304

Aquatic Acute 2 H401

Aquatic Chronic 3 H412

Full text of H-phrases: see section 16

2.2. Label Elements

GHS-US Labeling

Hazard Pictograms (GHS-US)



Signal Word (GHS-US)

: Danger

Hazard Statements (GHS-US)

: H304 - May be fatal if swallowed and enters airways.
H317 - May cause an allergic skin reaction.
H319 - Causes serious eye irritation.
H350 - May cause cancer.
H373 - May cause damage to organs through prolonged or repeated exposure.
H401 - Toxic to aquatic life.
H412 - Harmful to aquatic life with long lasting effects.

Precautionary Statements (GHS-US)

: P201 - Obtain special instructions before use.
P202 - Do not handle until all safety precautions have been read and understood.
P260 - Do not breathe vapors, mist, or spray.
P264 - Wash hands, forearms, and other exposed areas thoroughly after handling.
P272 - Contaminated work clothing must not be allowed out of the workplace.
P273 - Avoid release to the environment.
P280 - Wear protective gloves, protective clothing, and eye protection.
P301+P310 - If swallowed: Immediately call a poison center or doctor.
P302+P352 - If on skin: Wash with plenty of water.
P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308+P313 - If exposed or concerned: Get medical advice/attention.
P331 - Do NOT induce vomiting.
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.
P337+P313 - If eye irritation persists: Get medical advice/attention.
P362+P364 - Take off contaminated clothing and wash it before reuse.
P405 - Store locked up.
P501 - Dispose of contents/container in accordance with local, regional, national,

ARMSTRONG'S WOOD STAINS

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

and international regulations.

2.3. Other Hazards

Exposure may aggravate those with pre-existing eye, skin, or respiratory conditions.

2.4. Unknown Acute Toxicity (GHS-US)

No data available

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Substance

Not applicable

3.2. Mixture

Name	Product Identifier	%	Classification (GHS-US)
Proprietary Ingredient #1	Proprietary*	60 - 62	Asp. Tox. 1, H304 Aquatic Acute 2, H401
Proprietary Ingredient #2	Proprietary*	33	Not classified
Proprietary Ingredient #3	Proprietary*	2 - 7	Flam. Liq. 1, H224 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 Carc. 1B, H350 STOT SE 3, H336 STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Acute 2, H401 Aquatic Chronic 2, H411
Proprietary Ingredient #4	Proprietary*	0.4	Acute Tox. 4 (Oral), H302 Acute Tox. 3 (Inhalation:dust,mist), H331 Eye Dam. 1, H318 Skin Sens. 1, H317 STOT SE 3, H335 STOT RE 1, H372 Aquatic Acute 1, H400

The specific chemical identity has been withheld as a trade secret [29 CFR 1910.1200].

Full text of H-phrases: see section 16

SECTION 4: FIRST AID MEASURES

4.1. Description of First Aid Measures

First-aid Measures General: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice.

First-aid Measures After Inhalation: When symptoms occur: go into open air and ventilate suspected area. Obtain medical attention if breathing difficulty persists.

First-aid Measures After Skin Contact: Remove contaminated clothing. Drench affected area with water for at least 15 minutes. Obtain medical attention if irritation develops or persists.

First-aid Measures After Eye Contact: Rinse cautiously with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention.

First-aid Measures After Ingestion: Rinse mouth. Do NOT induce vomiting. Obtain medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/Injuries: Causes serious eye irritation. Skin sensitization. May cause cancer. May cause damage to organs through prolonged or repeated exposure.

Symptoms/Injuries After Inhalation: Prolonged exposure may cause irritation.

Symptoms/Injuries After Skin Contact: May cause an allergic skin reaction. Symptoms may include: Redness, pain, swelling, itching, burning, dryness, and dermatitis.

Symptoms/Injuries After Eye Contact: Causes serious eye irritation. Symptoms may include: Redness, pain, swelling, itching, burning, tearing, and blurred vision.

Symptoms/Injuries After Ingestion: May be fatal if swallowed and enters airways.

Chronic Symptoms: May cause cancer. May cause damage to organs through prolonged or repeated exposure.

4.3. Indication of Any Immediate Medical Attention and Special Treatment Needed

If exposed or concerned, get medical advice and attention.

ARMSTRONG'S WOOD STAINS

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 5: FIRE-FIGHTING MEASURES

5.1. Extinguishing Media

Suitable Extinguishing Media: Dry chemical powder, alcohol-resistant foam, carbon dioxide (CO₂).

Unsuitable Extinguishing Media: Do not use a heavy water stream. A heavy water stream may spread burning liquid.

5.2. Special Hazards Arising From the Substance or Mixture

Fire Hazard: Not considered flammable but may burn at high temperatures.

Explosion Hazard: Product is not explosive.

Reactivity: Hazardous reactions will not occur under normal conditions.

5.3. Advice for Firefighters

Precautionary Measures Fire: Exercise caution when fighting any chemical fire. Under fire conditions, hazardous fumes will be present.

Firefighting Instructions: Use water spray or fog for cooling exposed containers. In case of major fire and large quantities:

Evacuate area. Fight fire remotely due to the risk of explosion.

Protection During Firefighting: Do not enter fire area without proper protective equipment, including respiratory protection.

Other Information: Do not allow run-off from fire fighting to enter drains or water courses.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal Precautions, Protective Equipment and Emergency Procedures

General Measures: Do not get in eyes, on skin, or on clothing. Do not breathe vapor, mist or spray.

6.1.1. For Non-emergency Personnel

Protective Equipment: Use appropriate personal protection equipment (PPE).

Emergency Procedures: Evacuate unnecessary personnel. Stop leak if safe to do so.

6.1.2. For Emergency Responders

Protective Equipment: Equip cleanup crew with proper protection.

Emergency Procedures: Upon arrival at the scene, a first responder is expected to recognize the presence of dangerous goods, protect oneself and the public, secure the area, and call for the assistance of trained personnel as soon as conditions permit.

Eliminate ignition sources.

6.2. Environmental Precautions

Prevent entry to sewers and public waters. Avoid release to the environment.

6.3. Methods and Material for Containment and Cleaning Up

For Containment: Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.

Methods for Cleaning Up: Clean up spills immediately and dispose of waste safely. Absorb and/or contain spill with inert material. Transfer spilled material to a suitable container for disposal. Do not take up in combustible material such as: saw dust or cellulosic material. Contact competent authorities after a spill. AVOID SPONTANEOUS COMBUSTION! Place all rags and sponges in a water filled metal container after use to prevent spontaneous combustion. If you do not have a container use an empty stain can. Let the rags sit for at least one week. Saturate any large textiles like drop cloths or paper products used for drop sheets or spray guards with water. Wash clothes with stain on them - do not leave them lying around.

6.4. Reference to Other Sections

See Heading 8. Exposure controls and personal protection. See Section 13, Disposal Considerations.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for Safe Handling

Precautions for Safe Handling: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes, on skin, or on clothing. Do not breathe vapors, mist, spray. AVOID SPONTANEOUS COMBUSTION! Place all rags and sponges in a water filled metal container after use to prevent spontaneous combustion. If you do not have a container use an empty stain can. Let the rags sit for at least one week. Saturate any large textiles like drop cloths or paper products used for drop sheets or spray guards with water. Wash clothes with stain on them - do not leave them lying around.

Hygiene Measures: Handle in accordance with good industrial hygiene and safety procedures. Wash hands and other exposed areas with mild soap and water before eating, drinking, or smoking and again when leaving work.

7.2. Conditions for Safe Storage, Including Any Incompatibilities

Technical Measures: Comply with applicable regulations.

Storage Conditions: Store in a dry, cool place. Keep/Store away from direct sunlight, extremely high or low temperatures and incompatible materials. Store in a well-ventilated place. Keep container tightly closed.

Incompatible Products: Strong acids, strong bases, strong oxidizers.

7.3. Specific End Use(s)

WOOD STAIN

ARMSTRONG'S WOOD STAINS

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control Parameters

For substances listed in section 3 that are not listed here, there are no established exposure limits from the manufacturer, supplier, importer, or the appropriate advisory agency including: ACGIH (TLV), NIOSH (REL), or OSHA (PEL).

Proprietary Ingredient #3		
USA NIOSH	NIOSH REL (TWA) (mg/m ³)	350 mg/m ³
USA NIOSH	NIOSH REL (ceiling) (mg/m ³)	1800 mg/m ³ (15 min)
USA IDLH	US IDLH (ppm)	1100 ppm (10% LEL)
USA OSHA	OSHA PEL (TWA) (mg/m ³)	2000 mg/m ³
USA OSHA	OSHA PEL (TWA) (ppm)	500 ppm

8.2. Exposure Controls

Appropriate Engineering Controls

: Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Ensure adequate ventilation, especially in confined areas. Ensure all national/local regulations are observed.

Personal Protective Equipment

: Gloves. Protective clothing. Protective goggles. Insufficient ventilation: wear respiratory protection.



Materials for Protective Clothing

: Chemically resistant materials and fabrics.

Hand Protection

: Wear protective gloves.

Eye Protection

: Chemical safety goggles.

Skin and Body Protection

: Wear suitable protective clothing.

Respiratory Protection

: If exposure limits are exceeded or irritation is experienced, approved respiratory protection should be worn.

Other Information

: When using, do not eat, drink or smoke.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on Basic Physical and Chemical Properties

Physical State	: Liquid
Appearance	: Various stain colors
Odor	: SLIGHT SOLVENT
Odor Threshold	: No data available
pH	: No data available
Evaporation Rate	: No data available
Melting Point	: No data available
Freezing Point	: No data available
Boiling Point	: 375 - 420 °F (190.56 - 215.56 °C)
Flash Point	: 205 °F (96.11 °C)
Auto-ignition Temperature	: No data available
Decomposition Temperature	: No data available
Flammability (solid, gas)	: No data available
Vapor Pressure	: No data available
Relative Vapor Density at 20 °C	: No data available
Relative Density	: No data available
Solubility	: NONE IN WATER
Partition Coefficient: N-Octanol/Water	: No data available
Viscosity	: No data available

9.2. Other Information

VOC content : < 50

ARMSTRONG'S WOOD STAINS

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 10: STABILITY AND REACTIVITY

- 10.1. Reactivity:** Hazardous reactions will not occur under normal conditions.
- 10.2. Chemical Stability:** Stable under normal temperature and pressure.
- 10.3. Possibility of Hazardous Reactions:** Hazardous polymerization will not occur.
- 10.4. Conditions to Avoid:** Direct sunlight, extremely high or low temperatures, and incompatible materials.
- 10.5. Incompatible Materials:** Strong acids, strong bases, strong oxidizers.
- 10.6. Hazardous Decomposition Products:** Carbon oxides (CO, CO₂). Hydrocarbons.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information On Toxicological Effects

Acute Toxicity: Not classified

Proprietary Ingredient #3	
LD50 Oral Rat	> 4300 mg/kg
LD50 Dermal Rabbit	> 2000 mg/kg
ATE (Dust/Mist)	2.18 mg/l/4h
Proprietary Ingredient #4	
LD50 Oral Rat	1470 mg/kg
ATE (Dust/Mist)	0.50 mg/l/4h
Proprietary Ingredient #1	
LD50 Oral Rat	> 2000 mg/kg
LD50 Dermal Rabbit	> 4480 mg/kg

Skin Corrosion/Irritation: Not classified

Serious Eye Damage/Irritation: Causes serious eye irritation

Respiratory or Skin Sensitization: May cause an allergic skin reaction

Germ Cell Mutagenicity: Not classified

Carcinogenicity: May cause cancer

Proprietary Ingredient #3	
IARC group	3

Reproductive Toxicity: Not classified

Specific Target Organ Toxicity (Single Exposure): Not classified

Specific Target Organ Toxicity (Repeated Exposure): May cause damage to organs through prolonged or repeated exposure

Aspiration Hazard: May be fatal if swallowed and enters airways

Symptoms/Injuries After Inhalation: Prolonged exposure may cause irritation

Symptoms/Injuries After Skin Contact: May cause an allergic skin reaction. Symptoms may include: Redness, pain, swelling, itching, burning, dryness, and dermatitis

Symptoms/Injuries After Eye Contact: Causes serious eye irritation. Symptoms may include: Redness, pain, swelling, itching, burning, tearing, and blurred vision

Symptoms/Injuries After Ingestion: May be fatal if swallowed and enters airways

Chronic Symptoms: May cause cancer. May cause damage to organs through prolonged or repeated exposure

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Ecology - General : Toxic to aquatic life. Harmful to aquatic life with long lasting effects.

Proprietary Ingredient #3	
LC50 Fish 1	< 7.1 mg/l (Species: Pimephales promelas, Exposure time 96 h)
LC50 other aquatic organisms 1	2.7 mg/l LL50 96 hr (Kelp forest mysid shrimp)
EC50 Daphnia 1	6.9 mg/l (Exposure time: 48 h)
Proprietary Ingredient #4	
LC50 Fish 1	0.14 - 0.32 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [flow-through])
LC 50 Fish 2	0.049 - 0.079 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [flow-through])
Proprietary Ingredient #1	
LC50 Fish 1	79.6 mg/l (Exposure time: 96 h - Species: Brachydanio rerio [semi-static])
LC 50 Fish 2	3.2 mg/l (Exposure time: 96 h - Species: Pimephales promelas [semi-static])

ARMSTRONG'S WOOD STAINS

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

12.2. Persistence and Degradability

ARMSTRONG'S WOOD STAINS	
Persistence and Degradability	Not established.

12.3. Bioaccumulative Potential

ARMSTRONG'S WOOD STAINS	
Bioaccumulative Potential	Not established.

12.4. Mobility in Soil

 No additional information available

12.5. Other Adverse Effects

Other Information : Avoid release to the environment.

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Waste Disposal Recommendations: Dispose of contents/container in accordance with local, regional, national, and international regulations.

Ecology – Waste Materials: Avoid release to the environment. This material is hazardous to the aquatic environment. Keep out of sewers and waterways.

SECTION 14: TRANSPORT INFORMATION

14.1. In Accordance with DOT Not regulated for transport

14.2. In Accordance with IMDG Not regulated for transport

14.3. In Accordance with IATA Not regulated for transport

SECTION 15: REGULATORY INFORMATION

15.1 US Federal Regulations

ARMSTRONG'S WOOD STAINS	
SARA Section 311/312 Hazard Classes	Health hazard - Serious eye damage or eye irritation Health hazard - Respiratory or skin sensitization Health hazard - Carcinogenicity Health hazard - Specific target organ toxicity (single or repeated exposure) Health hazard - Aspiration hazard

Proprietary Ingredient #3

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Proprietary Ingredient #4

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Listed on United States SARA Section 313

SARA Section 313 - Emission Reporting	1.0 %
--	-------

Proprietary Ingredient #1

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Proprietary Ingredient #2

Listed on the United States TSCA (Toxic Substances Control Act) inventory

EPA TSCA Regulatory Flag	Y2 - Y2 - indicates an exempt polymer that is a polyester and is made only from reactants included in a specified list of low concern reactants that comprises one of the eligibility criteria for the exemption rule.
---------------------------------	--

15.2 US State Regulations

Proprietary Ingredient #3

U.S. - Massachusetts - Right To Know List

U.S. - New Jersey - Right to Know Hazardous Substance List

U.S. - Pennsylvania - RTK (Right to Know) List

Proprietary Ingredient #4

U.S. - New Jersey - Right to Know Hazardous Substance List

Proprietary Ingredient #2

U.S. - Pennsylvania - RTK (Right to Know) List

SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

Revision Date : 02/23/2018

ARMSTRONG'S WOOD STAINS

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Other Information

: This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200.

GHS Full Text Phrases:

Acute Tox. 3 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 3
Acute Tox. 4 (Oral)	Acute toxicity (oral) Category 4
Aquatic Acute 1	Hazardous to the aquatic environment - Acute Hazard Category 1
Aquatic Acute 2	Hazardous to the aquatic environment - Acute Hazard Category 2
Aquatic Chronic 2	Hazardous to the aquatic environment - Chronic Hazard Category 2
Aquatic Chronic 3	Hazardous to the aquatic environment - Chronic Hazard Category 3
Asp. Tox. 1	Aspiration hazard Category 1
Carc. 1B	Carcinogenicity Category 1B
Eye Dam. 1	Serious eye damage/eye irritation Category 1
Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A
Flam. Liq. 1	Flammable liquids Category 1
Skin Irrit. 2	Skin corrosion/irritation Category 2
Skin Sens. 1	Skin sensitization Category 1
STOT RE 1	Specific target organ toxicity (repeated exposure) Category 1
STOT RE 2	Specific target organ toxicity (repeated exposure) Category 2
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H224	Extremely flammable liquid and vapor
H302	Harmful if swallowed
H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H319	Causes serious eye irritation
H331	Toxic if inhaled
H335	May cause respiratory irritation
H336	May cause drowsiness or dizziness
H350	May cause cancer
H372	Causes damage to organs through prolonged or repeated exposure
H373	May cause damage to organs through prolonged or repeated exposure
H400	Very toxic to aquatic life
H401	Toxic to aquatic life
H411	Toxic to aquatic life with long lasting effects
H412	Harmful to aquatic life with long lasting effects

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

SDS US (GHS HazCom)